

# HS1013060G

## Electrical Characteristics

Material	Permeability ( $\mu$ )	AL $\pm$ 8% (nH/N <sup>2</sup> )	DCB (% min) @ 50 Oe	Coreloss (mW/cm <sup>3</sup> , max) @ 50kHz, 100G
HS	60	92	78.2	4.5

OD : 1013



## Core Dimensions

Dimensions		Uncoated		Coated		Color	Packaging
		(mm)	(inch)	(mm)	(inch)		
OD	(Max)	101.60	4.000	103.10	4.059	Black	Box Qty = 12 pcs
ID	(min)	57.20	2.252	55.70	2.193		
HT	(max)	13.60	0.535	14.90	0.587		

## Physical Characteristics

Cross Section (A)	Path Length ( $\ell$ )	Window Area (Wa)	Volume (V)	Breakdown Voltage (Vac)
2.972 cm <sup>2</sup>	24.27 cm	24.37 cm <sup>2</sup>	72.130 cm <sup>3</sup>	1,000
0.461 in <sup>2</sup>	9.56 in	4,808,939 cmil	4.401 in <sup>3</sup>	

## Winding Information

0% Winding length/turn (cm)		
7.720		
40% winding factor Surface Area (cm <sup>2</sup> )		
345.39		
40% Wound Di.(mm)		
OD	ID	HT
116.93	36.46	31.44

## Typical DC Bias Performance

